

SSC Series Cooling Conveyor



Water Cooled Conveyor E – Type & D - Type



Spec Model	Typical Max Output (Kg/Hr)	Conveyor Length (MM)	Cooling Roll length (MM)	Cooling Roll Dia (MM)	Crasher drive (Kw)	Roller drive (KW)	Overall Dimension (MM)
SSC-4080	200-300	4000	800	268	1.1	0.75	5010*1410*1820
SSC-5080	300-400	5000	800	268	1.1	0.75	6010*1410*1820
SSC-5100	400-500	5000	1000	268	1.1	1.1	6010*1610*1820
SSC-6100	500-600	6000	1000	268	1.1	1.1	7010*1610*1820
SSC-6120	600-800	6000	1200	268	1.1	1.1	7010*1810*1820

- Forward & Backward Motion (For Emergency case and cleaning time)
- Variable speed.
- Separate water inlet and outlet for cooling rolls
- Soft Water Closed circuit cooling system
- High cooling efficiency.
- Equipped with permanent cap at the crusher side for temporary accumulation of flakes during trolley changing process.
- Separate drive for crusher
- Easy to access pump, strainer and fitting for easy maintenance and repairing
- Online adjustable roller to adjust flake thickness (If necessary)

SSC Series Cooling Conveyor

- Hot dip galvanized structure.
- Powder Coating Top Coat
- Finger break type crusher
- Stainless Steel Fitting, Bolt & Nuts
- Trolley to be match with Mill ground feeding system
- Chrome-plating Cooling Roll
- CE & ISO Standard



Description		E	D
Chinese Brand (Made In China) Electrical Component		--	Included
European Brand (Made In China) Electrical Component		Included	--
Separate Drive for crusher		Included	--
Sandvik brand Stainless Steel belt (Made in China)		Included	---
NAUT brand Stainless Steel belt (Made in China)		---	Included
No. of trolley		3	2
Standard Spare Parts	Description	Quantity	Quantity
	Compressed spring	2	2
	Rotary joint	4	4
	Spray Nozzles	10	6
	Roller Terminal Strand	2	2
	Insertor	3	3
	Driven chain	1	1